



FenceBoom

Application Guide

The Canadyne **FenceBoom** is a convenient, economical boom for simple yet effective spill containment.

The **FenceBoom** provides excellent performance and durability, with minimal storage volume.

Offered in a range of sizes to accommodate varying conditions and requirements.



The Canadyne **FenceBoom** is a solid buoyancy, fence-type boom for spill containment and recovery operations.

Features and Benefits:

- **Rectangular closed cell foam** flotation for utmost reliability.
- Convenient fold points for **minimal storage volume**.
- **Internal stiffeners (PVC or Fiberglass)** to maintain freeboard and draft
- Wide range of **storage options**—pallets, containers, or boom reels.
- Optional aircraft cable upper tension member and heavier ballast chain provide **excellent stability** and **tensile strength**.
- Wide range of **PVC and Urethane fabrics** available.
- **ASTM, Shotgun or Universal** style marine grade aluminum boom connectors to mate with existing equipment inventories.

Canadyne Technologies Inc.

12400 Vulcan Way
Richmond, BC, V6V 1J8
CANADA

Phone: 604.247.2297
Fax: 604.247.2298
Email: info@canatec.com
Web: www.canatec.com

Canadyne FenceBoom Data Sheet



FenceBoom on trailer-mounted reel



FenceBoom in aluminum storage box
(removable lid and door, not shown)



FenceBoom packed in individual carry bags and loaded into containers for storage/shipping.

| | FenceBoom 18 | FenceBoom 24 | FenceBoom 36 |
|---------------------------|--------------------------|--------------------------|--------------------------|
| Part Number | 10235 | 10263 | 10264 |
| Overall Height | 18 in (457 mm) | 24 in (610 mm) | 36 in (915 mm) |
| Freeboard | 6 in (152 mm) | 8 in (203 mm) | 12 in (305 mm) |
| Draft | 12 in (305 mm) | 16 in (407 mm) | 24 in (610 mm) |
| Stiffeners | PVC | PVC | Fiberglass |
| Top Tension | Optional | Optional | Optional |
| Ballast Chain Size | 1/4 in (7.1 mm) | 5/16 in (8.3 mm) | 3/8 in (10.0 mm) |
| Boom Weight | 1.5 lbs/ft (2.2 kg/m) | 2.0 lbs/ft (3.0 kg/m) | 2.7 lbs/ft (4.0 kg/m) |

Standard Features

- 22 oz/yd² (750 gsm) heavy-duty PVC-coated polyester fabric, bright orange
- All seams radio-frequency (RF) welded
- Marine grade extruded aluminum ASTM style end connectors
- 50 foot (15.25m) section length
- Solid, closed-cell polyethylene (PE) foam flotation
- Internal stiffeners (PVC for Model 18 and 24, Fiberglass for Model 36)
- Black webbing handles every 10 feet (3m)
- Hot dipped galvanized ballast chain in fully enclosed pocket with drain holes
- Stainless steel hardware / fasteners
- Anchor points at midpoint and each end, marked by orange handles
- Full factory support for spares, repairs and technical assistance
- Double Layer fabric skirt

Optional Features

- Upgrade to heavier 28 oz/yd² (950 gsm) PVC or to a polyurethane fabric for increased abrasion resistance
- Increase boom strength by adding a top tension members (PVC coated galvanized cable, stainless steel cable, webbing)
- Universal-type or Shotgun-type aluminum end connectors
- Custom sizes, section lengths
- Custom screening of client name, logo or identifying marks

Recommended Accessories

- Towing Bridle and Tow Line
- Anchor Assembly systems

Storage Options

- Boom reels, storage/deployment containers, storage/carry bags

"The right solution... the first time"