

# SAFETY DATA SHEET

	1. Iden	tification	
Product identifier	Orange Oil Furniture Polish		
Other means of identification	None.		
Recommended use	Furniture Polish		
Recommended restrictions	None known.		
Manufacturer/Importer/Supplier/I	Distributor information		
Manufacturer			
Company name	Howard Products Inc.		
Address	560 Linne Road		
	Paso Robles, CA 93446 United States		
Telephone	Phone:	1-805-227-1000	
e-mail	Not available.		
Emergency phone number	Emergency Phone:	CHEMTREC: 1-800-424-9300	
Supplier	See above.		
	2. Hazard i	identification	
Physical hazards	Not classified.		
Health hazards	Sensitization, skin	Category 1	
Aspiration hazard Category 1	Category 1		
Environmental hazards	Not classified.		
Label elements			
Signal word	Danger		
Hazard statement	May be fatal if swallowed and enters airways. May cause an allergic skin reaction.		
Precautionary statement			
Prevention	Avoid breathing mist or vapour. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves.		
Response	IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash it before reuse. Specific treatment (see information on this label).		
Storage	Store locked up.		
Disposal	Dispose of container in accordance with local, regional, national and international regulations.		
Other hazards	None known.		
Supplemental information	None.		
	2. Commonition/info	rmation on ingredients	

#### Mixtures

Chemical name	Common name and synonyms	CAS number	%
Distillates (petroleum), hydrotreated heavy paraffinic		64742-54-7	65-85*
Distillates (petroleum), light hydrotreated		64742-47-8	10-30*
Oils, orange, sweet		8008-57-9	1-5*

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

**Composition comments** \*CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with the amended HPR as of April 2018.

	4. First-aid measures	
Inhalation	If symptoms develop move victim to fresh air. If symptoms persist, obtain medical attention.	
Skin contact	IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Specific treatment (see information on this label). Take off contaminated clothing and wash it before reuse.	
Eye contact	Flush with cool water. Remove contact lenses, if applicable, and continue flushing. Obtain mec attention if irritation persists.	
Ingestion	IF SWALLOWED: Immediately call a POISON CENTRE or doctor. Do NOT induce vomiting.	
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary oedema and pneumonitis. May cause an allergic skin reaction Dermatitis. Rash.	
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Symptoms may be delayed.	
General information	If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse. Avoid contact with eyes and skin. Keep out of reach of children.	
	5. Fire-fighting measures	
Suitable extinguishing media	Alcohol resistant foam. Powder. Carbon dioxide. Dry chemical.	
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.	
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.	
Hazardous combustion products	May include and are not limited to: Oxides of carbon.	
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.	
Fire fighting equipment/instructions	Cool containers exposed to heat with water spray and remove container, if no risk is involved.	
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.	
General fire hazards	Combustible. No unusual fire or explosion hazards noted.	
	6. Accidental release measures	
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapour. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.	
Methods and materials for containment and cleaning up	Use water spray to reduce vapours or divert vapour cloud drift. Prevent entry into waterways, sewer, basements or confined areas.	
	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.	
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.	
	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.	
Environmental precautions	Avoid discharge into drains, water courses or onto the ground. Do not discharge into lakes, streams, ponds or public waters.	
	7. Handling and storage	
Precautions for safe handling	Avoid breathing mist or vapour. Avoid contact with eyes, skin, and clothing. When using do not eat or drink. Use only in well-ventilated areas. Avoid prolonged or repeated contact with skin. Wear appropriate personal protective equipment. Wash thoroughly after handling. Use good industrial hygiene practices in handling this material.	
Conditions for safe storage, including any incompatibilities	Store locked up. Keep away from heat and sources of ignition. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS). Keep out of reach of children.	

### 8. Exposure controls/Personal protection

	Values		
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction.
Canada. Alberta OELs (Occu Components	upational Health & Safety ( Type	Code, Schedule 1, Table 2) Value	Form
Distillates (petroleum),	STEL	10 mg/m3	Mist.
hydrotreated heavy paraffinic (CAS 64742-54-7)			
	TWA	5 mg/m3	Mist.
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)	TWA	200 mg/m3	Vapour.
Canada. British Columbia Ol Safety Regulation 296/97, as		ure Limits for Chemical Substances, O	ccupational Health and
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	1 mg/m3	Mist.
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)	TWA	200 mg/m3	Non-aerosol.
Canada. Manitoba OELs (Re Components	g. 217/2006, The Workplac Type	e Safety And Health Act) Value	Form
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction.
• • • • • • • • • • • • • • • • • • •			
Canada. Quebec OELs. (Min Components	istry of Labour - Regulatio Type	n Respecting the Quality of the Work E Value	nvironment) Form
-			
Components Distillates (petroleum), hydrotreated heavy	Туре	Value	Form
Components Distillates (petroleum), hydrotreated heavy	Type STEL	Value           10 mg/m3           5 mg/m3           1590 mg/m3	Form Mist.
Components Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) Distillates (petroleum), light hydrotreated (CAS 64742-47-8)	Type STEL TWA TWA	Value           10 mg/m3           5 mg/m3           1590 mg/m3           400 ppm	Form Mist.
Components Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) Distillates (petroleum), light hydrotreated (CAS 64742-47-8) logical limit values	Type STEL TWA TWA	Value           10 mg/m3           5 mg/m3           1590 mg/m3	Form Mist.
Components Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) Distillates (petroleum), light hydrotreated (CAS 64742-47-8) logical limit values posure guidelines	Type STEL TWA TWA No biological exposure lim	Value           10 mg/m3           5 mg/m3           1590 mg/m3           400 ppm	Form Mist.
Components Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) Distillates (petroleum), light hydrotreated (CAS 64742-47-8) logical limit values posure guidelines Canada - Alberta OELs: Skin	Type STEL TWA TWA No biological exposure lim	Value 10 mg/m3 5 mg/m3 1590 mg/m3 400 ppm hits noted for the ingredient(s).	Form Mist.
Components Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) Distillates (petroleum), light hydrotreated (CAS 64742-47-8) logical limit values posure guidelines Canada - Alberta OELs: Skin Distillates (petroleum), lig 64742-47-8)	Type STEL TWA TWA No biological exposure lim a designation ht hydrotreated (CAS	Value           10 mg/m3           5 mg/m3           1590 mg/m3           400 ppm	Form Mist.
Components Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) Distillates (petroleum), light hydrotreated (CAS 64742-47-8) logical limit values tosure guidelines Canada - Alberta OELs: Skin Distillates (petroleum), lig 64742-47-8) Canada - British Columbia O Distillates (petroleum), lig	Type STEL TWA TWA No biological exposure lim designation ht hydrotreated (CAS DELs: Skin designation	Value 10 mg/m3 5 mg/m3 1590 mg/m3 400 ppm hits noted for the ingredient(s).	Form Mist.
Components Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) Distillates (petroleum), light hydrotreated (CAS 64742-47-8) logical limit values tosure guidelines Canada - Alberta OELs: Skin Distillates (petroleum), lig 64742-47-8) Canada - British Columbia O Distillates (petroleum), lig 64742-47-8)	Type STEL TWA TWA No biological exposure lim designation ht hydrotreated (CAS DELs: Skin designation ht hydrotreated (CAS	Value         10 mg/m3         5 mg/m3         1590 mg/m3         400 ppm         hits noted for the ingredient(s).         Can be absorbed through the skin.	Form Mist.
Components Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) Distillates (petroleum), light hydrotreated (CAS 64742-47-8) logical limit values tosure guidelines Canada - Alberta OELs: Skin Distillates (petroleum), lig 64742-47-8) Canada - British Columbia O Distillates (petroleum), lig	Type STEL TWA TWA No biological exposure lim designation ht hydrotreated (CAS DELs: Skin designation ht hydrotreated (CAS	Value         10 mg/m3         5 mg/m3         1590 mg/m3         400 ppm         hits noted for the ingredient(s).         Can be absorbed through the skin.	Form Mist.
Components Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) Distillates (petroleum), light hydrotreated (CAS 64742-47-8) Hogical limit values nosure guidelines Canada - Alberta OELs: Skin Distillates (petroleum), lig 64742-47-8) Canada - British Columbia O Distillates (petroleum), lig 64742-47-8) Canada - Saskatchewan OEL Distillates (petroleum), lig	Type STEL TWA TWA WA No biological exposure lim designation ht hydrotreated (CAS DELs: Skin designation ht hydrotreated (CAS Ls: Skin designation ht hydrotreated (CAS Cood general ventilation (1 should be matched to como or other engineering control	Value         10 mg/m3         5 mg/m3         1590 mg/m3         400 ppm         hits noted for the ingredient(s).         Can be absorbed through the skin.         Can be absorbed through the skin.	Form Mist. Mist. De used. Ventilation rates res, local exhaust ventilation mmended exposure limits.
Components Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) Distillates (petroleum), light hydrotreated (CAS 64742-47-8) logical limit values osure guidelines Canada - Alberta OELs: Skin Distillates (petroleum), lig 64742-47-8) Canada - British Columbia O Distillates (petroleum), lig 64742-47-8) Canada - Saskatchewan OEI Distillates (petroleum), lig 64742-47-8) Canada - Saskatchewan OEI Distillates (petroleum), lig 64742-47-8) oropriate engineering	Type STEL STEL TWA TWA No biological exposure lim designation ht hydrotreated (CAS DELs: Skin designation ht hydrotreated (CAS Ls: Skin designation ht hydrotreated (CAS Case Construction ( should be matched to com- or other engineering contri- exposure limits have not b	Value           10 mg/m3           5 mg/m3           1590 mg/m3           400 ppm           hits noted for the ingredient(s).           Can be absorbed through the skin.           It is a plicable, use process enclosu           It is to maintain airborne levels below reconseen established, maintain airborne levels	Form Mist. Mist. De used. Ventilation rates res, local exhaust ventilation mmended exposure limits.
Components Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) Distillates (petroleum), light hydrotreated (CAS 64742-47-8) logical limit values posure guidelines Canada - Alberta OELs: Skin Distillates (petroleum), lig 64742-47-8) Canada - British Columbia O Distillates (petroleum), lig 64742-47-8) Canada - Saskatchewan OEI Distillates (petroleum), lig 64742-47-8) Canada - Saskatchewan OEI Distillates (petroleum), lig 64742-47-8) canada - British Columbia O Distillates (petroleum), lig 64742-47-8) oropriate engineering trols	Type STEL STEL TWA TWA No biological exposure lim designation ht hydrotreated (CAS DELs: Skin designation ht hydrotreated (CAS Ls: Skin designation ht hydrotreated (CAS Case Construction ( should be matched to com- or other engineering contri- exposure limits have not b	Value           10 mg/m3           5 mg/m3           1590 mg/m3           400 ppm           hits noted for the ingredient(s).           Can be absorbed through the skin.           It is a policiable, use process enclosu           It is maintain airborne levels below recordered	Form Mist. Mist. De used. Ventilation rates res, local exhaust ventilation mmended exposure limits.
Components Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) Distillates (petroleum), light hydrotreated (CAS 64742-47-8) logical limit values osure guidelines Canada - Alberta OELs: Skin Distillates (petroleum), lig 64742-47-8) Canada - British Columbia O Distillates (petroleum), lig 64742-47-8) Canada - Saskatchewan OEI Distillates (petroleum), lig 64742-47-8) canada - Saskatchewan OEI Distillates (petroleum), lig 64742-47-8) canada - Saskatchewan OEI Distillates (petroleum), lig 64742-47-8) oropriate engineering trols	Type STEL TWA TWA TWA No biological exposure lime designation ht hydrotreated (CAS DELs: Skin designation ht hydrotreated (CAS Ls: Skin designation ht hydrotreated (CAS CAS CAS CAS CAS CAS CAS CAS CAS CAS	Value           10 mg/m3           5 mg/m3           1590 mg/m3           400 ppm           hits noted for the ingredient(s).           Can be absorbed through the skin.           It is a policiable, use process enclosu           It is maintain airborne levels below recordered	Form Mist. Mist. De used. Ventilation rates res, local exhaust ventilation mmended exposure limits.

Impervious gloves. Confirm with reputable supplier first.

Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. As required by employer code.		
Respiratory protection	Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).		
Thermal hazards	Not applicable.		
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace. When using do not eat or drink.		

## 9. Physical and chemical properties

Appearance	Clear
Physical state	Liquid.
Form	Liquid.
Colour	Orange
Odour	Orange
Odour threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	> 204.44 °C (> 400 °F)
Flash point	163.3 °C (326.0 °F) TCC
Evaporation rate	< 1 (BuAc=1)
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit – upper (%)	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (Water)	Negligible
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.
Specific gravity	0.86
	10. Stability and reactivity

Reactivity	This product may react with strong oxidising agents.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Do not mix with other chemicals.
Incompatible materials	Strong oxidising agents.
Hazardous decomposition products	May include and are not limited to: Oxides of carbon.

#### 11. Toxicological information

Information on likely routes of Inhalation	exposure Prolonged inhalation may be harmful.		
Skin contact			
	May cause an allergic skin reaction.		
Eye contact Ingestion	Direct contact with eyes may cause temporary irritation. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious		
	chemical pneumonia. May cause stomach distress, nausea or vomiting.		
Symptoms related to the physical, chemical and toxicological characteristics	Aspiration may cause pulmonary oedema and pneumonitis. May cause an allergic skin reaction. Dermatitis. Rash.		
Information on toxicological ef	ffects		
Acute toxicity	May be fatal if swallowed and enters airways. May cause an allergic skin reaction.		
Components	Species	Test results	
Distillates (petroleum), hydrotrea	ated heavy paraffinic (CAS 64742-54-7)		
Acute			
Dermal	Rabbit	5000 mg/kg 24 Hours ECHA	
LD50	Rabbit	> 5000 mg/kg, 24 Hours, ECHA	
		> 2000 mg/kg, 24 Hours, ECHA	
Inhalation LC50	Rat	> 5.5 mg/L, 4 Hours, ECHA	
LC30	Nat	-	
		> 5.3 mg/L, 4 Hours, ECHA	
		> 5.2 mg/L, 4 Hours, ECHA	
Oral LD50	Rat	> 5000 mg/kg, ECHA	
LDJU	Nat		
<b>-</b>		> 2000 mg/kg, ECHA	
Distillates (petroleum), light hydr	otreated (CAS 64742-47-8)		
<b>Acute</b> Dermal			
LD50	Rabbit	> 4000 mg/kg, 24 Hours, ECHA	
		> 2000 mg/kg, 24 Hours, ECHA	
Inhalation		2 2000 mg/kg, 2 moulo, 20m/k	
LC50	Cat	> 6.4 mg/L, 6 Hours, ECHA	
	Rat	> 7.5 mg/L, 6 Hours, ECHA	
		> 6 mg/L, 4 Hours, ECHA	
		> 5.7 mg/L, 4 Hours, ECHA	
		> 5.3 mg/L, 4 Hours, ECHA	
		> 5.3 mg/L, 4 Hours, ECHA	
		> 5.2 mg/L, 4 Hours, ECHA	
		> 4.6 mg/L, 4 Hours, ECHA	
		> 4.5 mg/L, 4 Hours, ECHA	
		> 4.3 mg/L, 4 Hours, ECHA	
		> 0.1 mg/L, 8 Hours, ECHA	
		5.2 mg/l/4h, LOLI	
Oral			
LD50	Rat	> 20000 mg/kg, ECHA	
		> 25 ml/kg, HSDB	
Oils, orange, sweet (CAS 8008-	57-9)		
Acute			
Dermal			
LD50	Rat	> 5000 mg/kg, RTECS	

_				
Components	Species Test results			
Inhalation LC50	Not avail	able		
Oral	_			
LD50	Rat		> 5000 mg/kg, RTECS	
kin corrosion/irritation	Prolonged	skin contact may cause temporary irritation	on.	
Exposure minutes	Not availab	ole.		
Erythema value	Not available.			
Oedema value	Not availab	Not available.		
Serious eye damage/eye rritation	Direct conta	act with eyes may cause temporary irritat	ion.	
Corneal opacity value	Not availab	ble.		
Iris lesion value	Not availab	Not available.		
Conjunctival reddening value	Not availab	le.		
Conjunctival oedema value	<ul> <li>Not availab</li> </ul>	Not available.		
Recover days	Not availab	ble.		
Respiratory or skin sensitisatio	on			
Respiratory sensitisation	Not a respi	ratory sensitizer.		
Skin sensitisation	May cause	an allergic skin reaction.		
Germ cell mutagenicity	No data av	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	-	Not classified.		
Reproductive toxicity	This produ-	ct is not expected to cause reproductive of	or developmental effects.	
Specific target organ toxicity - single exposure	Not classifi			
Specific target organ toxicity - repeated exposure	Not classifi	ed.		
Aspiration hazard	May be fata	al if swallowed and enters airways.		
Chronic effects	Prolonged	inhalation may be harmful. Prolonged exp	posure may cause chronic effects.	
Further information	Not availab	ble.		
		12. Ecological information		
Ecotoxicity	See below			
Ecotoxicological data				
Components		Species	Test results	
Distillates (petroleum), hydrotreat	ted heavy para	affinic (CAS 64742-54-7)		
Crustacea	EC50	Daphnia	1000 mg/L, 48 Hours	
Distillates (petroleum), light hydro Aquatic	otreated (CAS	64742-47-8)		
Crustacea	EC50	Water flea (Daphnia pulex)	2.7 - 5.1 mg/L, 48 hours	
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.9 mg/L, 96 hours	
Persistence and degradability	No data is	available on the degradability of this prod	uct.	
Bioaccumulative potential				
Mobility in soil	No data av	ailable.		
Mobility in general	Not availab	Not available.		
Other adverse effects		No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		
		13. Disposal considerations		
<b>Disposal instructions</b>		I reclaim or dispose in sealed containers ontainer in accordance with local/regional	at licensed waste disposal site. Dispose of /national/international regulations.	
Local disposal regulations		accordance with all applicable regulation	-	
Hazardous waste code	-	code should be assigned in discussion b	etween the user, the producer and the wast	
#20370		Page: 6 of 7	Issue date 06-September-2019	

Waste from residues / unused	Dispose of in accordance with local regulations. Empty contained	ers or liners may retain some		
products	product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).			
Contaminated packaging	g Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.			
	14. Transport information			
General	Canada: TDG Proof of Classification: Classification Method: Cla 2.1 – 2.8 of the Transportation of Dangerous Goods Regulations name and the classification of the product will appear below.			
Transportation of Dangerous Go Not regulated as dangerous g				
	15. Regulatory information			
Canadian federal regulations	This product has been classified in accordance with the hazard contains all the information required by the HPR.	criteria of the HPR and the SDS		
Canada NPRI VOCs with Ade	ditional Reporting Requirements: Mass reporting threshold/Id	lentification Number		
Distillates (petroleum), lig 64742-47-8)				
Export Control List (CEPA 1 Not listed.	999, Schedule 3)			
Greenhouse Gases				
Not listed.				
Precursor Control Regulatio	ns			
Not regulated.				
WHMIS status	Controlled			
International regulations				
Inventory status				
Country(s) or region	Inventory Name	On Inventory (Yes/No)*		
Canada	Domestic Substances List (DSL)	Yes		
Canada	Non-Domestic Substances List (NDSL)	No		
*A "Yes" indicates that all compor	nents of this product comply with the inventory requirements administered	by the governing country(s)		
	16. Other information			
LEGEND	HEALTH * 2			
Severe 4	FLAMMABILITY 1			
Serious 3				
Moderate 2	PHYSICAL HAZARD 0			
Slight 1	PERSONAL X			
Minimal 0				
Issue date	06-September-2019			
Revision date	06-September-2019			
Effective date	06-September-2019			
Version No.	02			
Other information	For an updated SDS, please contact the supplier/manufacturer document.	listed on the first page of the		
Disclaimer	The information in the safety data sheet was written by Dell Tec (www.delltech.com) based on the best knowledge and experien contained herein was obtained from sources considered technic every effort has been made to ensure full disclosure of product I available and is so stated. Since conditions of actual product us supplier, it is assumed that users of this material have been fully requirements of all applicable legislation and regulatory instrum- implied, is made and supplier will not be liable for any losses, in which may result from the use of or reliance on any information	ce currently available. Information cally accurate and reliable. While hazards, in some cases data is not e are beyond control of the y trained according to the ents. No warranty, expressed or juries or consequential damages		
Prepared by	Dell Tech Laboratories Ltd. Phone: (519) 858-5021			